

# Mini excavator CDM855

457500 € fara TVA

[Click aici sa vezi produsul](#)



<b>DE BAZ?</b>	Capacitate galeata	3 m <sup>3</sup>
Sarcina utila nominala	5000 kg	
Greutate de operare	16800(16600 HD)±300kg	
Forta de tractiune	155±3k N	
Forta de eruptie	155±3k N	
LxLxA	7870x3000x3380mm	
<b>MOTOR</b>	Producator/Model	WEICHAI/WD10G220E21
Putere nominala	162 kW/2200 rpm	
Cuplu maxim	860 N·m/1400-1600 rpm	
Alezajul x cursa	126x130 mm	
Nr. de cilindri/deplasare	6/9.726L	
Purificator de aer	Filtru de aer in trei etape	
Alternator	70Amp	
Baterie	2-24V/ 120Ah	
Starting Motor	24V/7.5kW	
<b>DRIVE TRAIN</b>	Transmission Type	Planetary Powershift
Shift Type	Mechanical Powershift Control	
Pressure of Transmission	1. 1-1.5MPa	
Torque Converter Type	Single-stage,Duo-turbine,4-element	
Axles	Rigid (Front)&Oscillating (Rear)	
Rear Axle Oscillation	± 10°	
Differential	Conventional	
Main Reducer	Spiral Bevel, 1-stage Reduction	
Final Reducer	Planetary Reduction	

D85-25 L-3 16PR TT		
Travel Speed-Forward	11.5/36 km/h	
Travel Speed-Reverse	16 km/h	
<b>BRAKE SYSTEM</b>	Service Brake	Single Circuit Caliper, Dry Brake
Setting Pressure	0.70-0.78MPa	
Parking Brake	Flexible Shaft Controlled Caliper Brake	
Emergency Brake		
<b>STEERING SYSTEM</b>	Type	Hydraulic Load Sensing System
Pump	176L/min·2200rpm	
System Pressure	15MPa	
Cylinder Type	Double Acting	
Steering Angle	±35°	
<b>HYDRAULIC SYSTEM</b>	Type	Joystick Control (Single-lever)
Pump	220L/min·2200rpm	
Control Valve	2 Spool	
System Pressure	16MPa	
Durata ciclului	11.5	
<b>CAPACITATE DE REUMPLIRE DE SERVICE</b>	Rezervor de combustibil	280L
Rezervor hidraulic	245/250(a treia bobina)L	
Arbore cotit	20L	
Transmitere	46L	

~~28L~~  
fata/axa  
spate







SC Stivuitoare-Lize SRL

Telefon: +40 744 891 111

Email: [office@stivuitoarenoi.ro](mailto:office@stivuitoarenoi.ro)

Website: <https://stivuitoarenoi.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania