

Mini excavator CDM855

91500 € fara TVA

[Click aici sa vezi produsul](#)



DE BAZ?	Capacitate galeata	3 m ³
Sarcina utila nominala	5000 kg	
Greutate de operare	16800(16600 HD)±300kg	
Fora de tractiune	155±3k N	
Fora de eruptie	155±3k N	
LxLxA	7870×3000×3380mm	
MOTOR	Producator/Model	WEICHAI/WD10G220E21
Putere nominala	162 kW/2200 rpm	
Cuplu maxim	860 N·m/1400-1600 rpm	
Alezajul x cursa	126×130 mm	
Nr. de cilindri/deplasare	6/9.726L	
Purificator de aer	Filtru de aer in trei etape	
Alternator	70Amp	

2-24V/ 120Ah		
Baterie		
Starting Motor	24V/7.5kW	
DRIVE TRAIN	Transmission Type	Planetary Powershift
Shift Type	Mechanical Powershift Control	
Pressure of Transmission	1. 1-1.5MPa	
Torque Converter Type	Single-stage,Duo-turbine,4-element	
Axles	Rigid (Front)&Oscillating (Rear)	
Rear Axle Oscillation	± 10°	
Differential	Conventional	
Main Reducer	Spiral Bevel, 1-stage Reduction	
Final Reducer	Planetary Reduction	
Tire	23.5-25 L-3 16PR TT	
Travel Speed-Forward	11.5/36 km/h	
Travel Speed-Reverse	16 km/h	
BRAKE SYSTEM	Service Brake	Single Circuit Caliper, Dry Brake
Setting Pressure	0.70-0.78MPa	
Parking Brake	Flexible Shaft Controlled Caliper Brake	
Emergency Brake		
STEERING SYSTEM	Type	Hydraulic Load Sensing System
Pump	176L/min-2200rpm	
System Pressure	15MPa	
Cylinder Type	Double Acting	
Steering Angle	±35°	
HYDRAULIC SYSTEM	Type	Joystick Control (Single-lever)
Pump	220L/min-2200rpm	
Control Valve	2 Spool	
System Pressure	16MPa	
Durata ciclului	11.5	
CAPACITATE DE REUMPLIRE DE SERVICE	Rezervor de combustibil	280L
Rezervor hidraulic	245/250(a treia bobina)L	
Arbore cotit	20L	

76
Transmitter

~~281~~/28L
fata/axa
spate



SC Stivuitoare-Lize SRL

Telefon: +40 744 891 111

Email: office@stivuitoarenoi.ro

Website: <https://stivuitoarenoi.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania