

Mini excavator CDM860

635000 € fara TVA

[Click aici sa vezi produsul](#)



BASIG

Capacitate galeata	3,5 m ³
Sarcina utila nominala	6000 kg
Greutate de operare	20850±300kg
Fora de tractiune	175±3kN
Fora de eruptie	200±3kN
LxLxA	8610×3050×3430mm
Producator/Model	WEICHAH/WD10G240E21
Putere nominala	175 kW/2200 rpm
Cuplu maxim	920N ·m/1300-1600rpm
Alezajul x cursa	126×130 mm
No.of Cylinders / Displacement	6/9.726L
Air Cleaner	Three Stage Air Cleaner
Altemator	55Amp
Battery	2-24V/120Ah
Starting Motor	24V/7.5kW
Transmission Type	Countershaft Powershift
Shift Type	Electronic Powershift Contro
Pressure of Transmission	1.1-1.5MPa
Torque Converter Type	Single-stage & turbine,3-element
Axles	Rigid(Front) & Oscillating (Rear)
Rear Axle Oscillation	±10°
Differential	Conventiona

MOTOR**DRIVE TRAIN**

	Spiral Bevel, 1-stage Reduction Reducer	
	Final Reducer	Planetary Reduction
	Tire	23.5-25 L-320PR TT
	Travel Speed-Forward	6.7/11.7/23.8/37.5 km/h
	Travel Speed-Reverse	6.7/11.7/23.8 km/h
BRAKE SYSTEM	Service Brake	Single Circuit Caliper, Dry Brake
	Setting Pressure	0.70-0.78MPa
	Parking Brake	Hydraulic Actuated Drum Brake
	Emergency Brake	Hydraulic Actuated Drum Brake
	Type	Hydraulic Load Sensing System
STEERING SYSTEM	Pump	176L/min ·220Orpm
	System Pressure	16MPa
	Cylinder Type	Double Acting
	Steering Angle	±35°
	Tip	Control cu joystick (cu o singura maneta)
	Pompa	275L/min ·220Orpm
SISTEM HIDRAUIC	Supapa de control	2 Spoo
	Presiunea sistemului	16MPa
	Durata ciclului (sec.)	11.8
	Rezervor de combustibil	285L
	Rezervor hidraulic	270/275(a treia bobina)L
CAPACITATE DE REUMPLIRE DE SERVICE	Arbore cotit	20L
	Transmitere	32L

31a/31L
fata/axa
spate



SC Stivuitoare-Lize SRL

Telefon: +40 744 891 111

Email: office@stivuitoarenoi.ro

Website: <https://stivuitoarenoi.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania