

Motostivuator Lonking Diesel LG30DT 3 tone, catarg duplex, cu cabina

21400 € fara TVA

[Click aici sa vezi produsul](#)



| 0 | 1 | 2 | 3 | 6 | |
|------|--|------------|------|----------------------------------|---------|
| | 1.01 | Producator | | | LONKING |
| 1.02 | Model | | | LG30DT? | |
| 1.03 | Tip de putere | | | Motorina | |
| 1.04 | Capacitatea nominala | Q | kg | 3000 | |
| 1.05 | Centrul de incarcare | J | mm | 500 | |
| 2.01 | STD Inaltime maxima (cu spatari) | | mm | 4210 | |
| 2.02 | STD Inaltimea maxima de ridicare | h1 | mm | 3000 | |
| 2.03 | Inaltimea protectiei deasupra capului | h4 | mm | 2150 | |
| 2.04 | Lungime totala (cu furca) | L1 | mm | 3850 | |
| 2.05 | Ampatament | L2 | mm | 1750 | |
| 2.06 | Consola frontala | L3 | mm | 487 | |
| 2.07 | Consola din spate | L4 | mm | 550 | |
| 2.08 | Garda min. la sol (cadru/catarg) | m1/m2 | mm | 165/132 | |
| 2.09 | Latimea totala | W1 | mm | 1250 | |
| 2.10 | Gama de reglare a furcii (in exterior) | | mm | 255-1055 | |
| 2.11 | Dimensiunea furcii STD (L5*W*T) | | mm | 1070x125x45 | |
| 2.12 | Banda de rulare a rotii din fata | S | mm | 1030 | |
| 2.13 | Banda de rulare a rotii din spate | P | mm | 980 | |
| 2.14 | Min.raza de viraj | R1 | mm | 2520 | |
| 2.15 | Latimea minima a culoarului pentru paleti 1000x1200, transversal | | mm | 4200 | |
| 2.16 | Latimea minima a culoarului pentru paleti 800x1200, pe lungime | | mm | 4407 | |
| 3.01 | Numar roti, fata/spate (X=roti antrenate) | | | X=2/2 | |
| 3.02 | Tip anvelope | | | Pneumatic | |
| 3.03 | Dimensiunea anvelopelor, fata | | | 28x9-15-14PR | |
| 3.04 | Dimensiunea anvelopelor, spate | | | 6.50-10-10PR | |
| 4.01 | Viteza max.de deplasare, incarcata/descarcata | | km/h | 18,5/20 | |
| 4.02 | Viteza maxima de ridicare, incarcata/descarcata | | mm/s | 450/485 | |
| 4.03 | Viteza de scadere, incarcata/descarcata | | mm/s | Incarcat? 600/Neincarcata ? 300 | |
| 4.04 | Max.gradient, incarcata/descarcata | | % | 20 | |
| 4.05 | Greutate operationala STD (cu ulei si apa) | | kg | 4160 | |
| 4.06 | Incarcare osii, fata/spate (incarcata) | | kg | 6520/640 | |
| 4.07 | Incarcare osii, fata/spate (descarcata) | | kg | 1680/2480 | |
| 4.08 | Frâna de serviciu | | | Pedala de frâna mecanica/putere | |
| 4.09 | Frâna de parcare | | | Maneta de frana de mana mecanica | |
| 4.10 | Tipul de unitate | | | Mecanic/Automat | |
| 4.11 | Capacitatea rezervorului de combustibil | | L | 60 | |
| 4.12 | Voltaj/capacitate baterie | | V/Ah | 12/80 | |



SC Stivuitoare-Lize SRL

Telefon: +40 744 891 111

Email: office@stivuitoarenoi.ro

Website: <https://stivuitoarenoi.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania