

# Motostivuator de teren diesel 3.5 tone, inaltime catarg 3m

152000 € fara TVA

[Click aici sa vezi produsul](#)





**LONKING 龙工**



## CPCD35-NR20Y4/NR22Y4 LG Series

No.	Model	Code	Unit	CPCD35	
1	Powertype			Diesel	
2	Rated capacity		kg	3500	
3	Load center	J	mm	500	
4	STD Maxlifting height	h1	mm	3000	
5	Free Lifting height	h3	mm	150	
6	STD Fork size	LS x W x T	mm	1220 x 122 x 50	
7	Adjusting range of fork (outside)		mm	250-3500	
8	Mast inclination		deg	front 10 rear 12	
9	Front overhang	L3	mm	600	
10	Rear overhang	L4	mm	612	
11	Dimensions	Overall length (without fork)	L1	mm	3092
12		Overall width	W1	mm	1600
13		Lowered mast height	h2	mm	2350
14		STD Maxheight (with backrest)		mm	4230
15		Overhead guard height	h4	mm	2320
16	Min turning radius	R1	mm	3365	
17	Min right angle stacking aisle width	Ra	mm	5100	
18	Max traveling speed loaded/unloaded		Km/h	18/19	
19	Max lifting speed loaded		mm/s	380	





22	STD operating weight (with oil & water)			kg	5545	
23	Bridge load	loaded	Front	kg	7872	
24			Rear	kg	1073	
25		unloaded	Front	kg	2345	
26			Rear	kg	3100	
27	Tires	Tires size, front			14-17.5-14PR	
28		Tires size, rear			10.0/75-15.3-14PR	
29	Tread	Front wheel tread		S	mm	1250
30		Rear wheel tread		P	mm	1190
31	Wheelbase		L2	mm	1880	
32	Min ground clearance		Mast	mm	270	
33			Frame	mm	226	
Specifications						
34	Engine model				YUNNEI DEF20CDF4(Euro V) YUNNEI YN30NAG4(CHN IV)	
35	Rated power/speed			kW/rpm	45/2400 36.8/2500	
36	Max torque/speed			N·m/rpm	233/1500-1800 200/1400-1750	
37	Emissions			L	2 2.977	
40	Transmission type		Electrical controlled hydraulic transmission			
41	Gear		front 2, rear 1			

## Performance and Features:



More powerful



engine

The full-suspension hydraulic transmission is equipped with the function of switching between 2-wheel drive and 4-wheel drive, which can improve the driving speed and climbing degree of the forklift.



More reliable



Reinforced drive axle

The drive axle is equipped with tires with wide base depth and reinforced steering axle, which can better adapt to special working conditions.



More convenient



New instrument

The newly developed LCD instrument has more refined functions and more stable performance. It can fully display all the status of the forklift, fault codes and other important information, the operator can intuitively understand the status of the forklift and facilitate maintenance.



More comfortable



pilothouse

The full-suspension roof guard equipped with rubber shock pads replaces the traditional rigid design, which greatly reduces the vibration of the forklift body, reduces operator fatigue, and makes the forklift run more smoothly on rough terrain.



More efficient



Gantry

The wide-view mast provides better forward vision, improves work efficiency, and ensures the safe operation of the forklift.





Termen de livrare: 90 zile





SC Stivuitoare-Lize SRL

Telefon: +40 744 891 111

Email: [office@stivuitoarenoi.ro](mailto:office@stivuitoarenoi.ro)

Website: <https://stivuitoarenoi.ro/>

Comuna Corunca, Str. Principala, nr. 412-413, judet Mures, Romania